

# brilliante finish

## Acrylic High Build Basecoat and Finish



BRILLIANTE FINISH is an acrylic polymer based, slightly translucent, trowel or knife applied plaster finish with subtle mottling.

### Uses:

BRILLIANTE Finish may be used for interior applications over properly prepared substrates, including new level 5 drywall or properly prepared existing drywall. Ultrakote's L5 is a preferred base coat for existing drywall.

### Benefits:

- 100% dust free
- Tintable
- Durable
- No sanding required
- Excellent yield, cost effective
- Minimal surface preparation
- Knife, sprayed, trowel or rolled
- Easily repairable

### Surface Preparation:

Surface must be clean, dry, sound and free of contaminants, oil, mildew and efflorescence. Ambient conditions, substrate and the product itself must be at above 40°F and rising during application.

### Product Specifications:

#### Packaging:

1 gallon plastic pail.

#### Coverage:

250 - 300 sq. ft. (23.22 - 27.87 m. sq.) per gallon.

#### Color:

12 standard colors.  
Custom colors available upon request.

#### Storage:

Store in a cool, dry interior place. Keep from freezing, out of direct sunlight for long periods and at no time expose to moisture, rain or snow. Storage temperature ranges between 40°F and 95°F.

#### Clean up:

Clean tools and equipment with water immediately after use.

#### Shelf Life:

1 year

# brilliante finish

## Acrylic High Build Basecoat and Finish

### Mixing:

A small amount of clean potable water may be added to adjust consistency. Always mix Brilliante Finish prior to addition of any water.

### Application:

BRILLIANTE Finish may be applied over level 5 drywall or a basecoat of Ultrakote L5 can also be used prior to application of BRILLIANTE Finish. Once basecoat has dried, apply a very thin coat of BRILLIANTE Finish with a Venetian trowel using short overlapping trowel strokes. Trowel in a random manner, using no straight vertical or horizontal trowel strokes. Allow to dry to the touch before applying subsequent coats. Once first coat has dried apply second coat in same manner, using short overlapping trowel strokes. As the second coat of BRILLIANTE Finish starts to dry it may be burnished with a clean, dry Venetian trowel. For highest polish it is best to burnish BRILLIANTE Finish at two stages: once when semi-wet and once when almost completely dry. If a higher sheen or more mottling is desired, a third coat may be applied, repeating the process of the second coat. When stopping application of BRILLIANTE Finish mid-wall, feather out the finish to a minimal thickness in a very irregular pattern to prevent a cold joint from appearing when application is resumed. After 24 hours a sealer or wax may be applied to deepen color and add durability.

### Curing / Drying:

BRILLIANTE Finish may take several hours to dry to its final appearance. Surface absorption, temperature and humidity will affect drying time. Protect from excessive traffic or moisture for 24 hours.

### Limitations:

Brilliante Finish should be applied when surface and ambient air conditions are between 40°F and 95°F.

### Technical Data:

Surface burning ASTM E 84 (class A)	Flame spread index:20 Smoke developed index: 5
Mildew/Mold resistance ASTM D 3273	9-10
Water vapor transmission ASTM D 1653	23.9 perms
VOC (g/L)	> 20 g/l

#### Precaution:

KEEP OUT OF THE REACH OF CHILDREN.

Not for internal consumption.

Do not apply in non-ventilated areas.

Use protective equipment such as gloves, eye protection and clothing.

#### First Aid:

In case of eye contact, flush with water at least 15 minutes.

In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION.

Remove and wash contaminated clothing.

If inhalation causes physical discomfort, remove to fresh air. If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK MEDICAL ATTENTION.

For additional information refer to the material Safety Data Sheet (MSDS).

#### Disposal:

Dispose of in accordance with local, state or federal regulations.

#### Warning:

KEEP OUT OF THE REACH OF CHILDREN.

NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE ONLY.

#### Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

#### Prop 65:

This product contains material listed by the state of California known to cause cancer, birth defects or other reproductive harm.

#### Technical support:

For technical support call 1-602-272-5830. Information contained in this product Information Guide conforms to the standard detail recommendations and specifications for the installations of Ultrakote Products as of the date published on this document. Ultrakote Products, Inc. assumes no liability, expressed or implied, as to architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact Ultrakote Products, Inc. or visit website at: [www.ultrakoteproducts.com](http://www.ultrakoteproducts.com)