

tuscan stain



TUSCAN STAIN is a pigmented acrylic sealer used in combination with Ultrakote acrylic finishes to achieve an “old world” or “antique” appearance. Tuscan Stain can also be used without pigment as a sealer.

Uses:

Tuscan Stain creates an “antiquing appearance” when applied to acrylic based or cement based stucco finishes.

Benefits:

- Weather resistant
- Resists dirt accumulation and staining
- Sealer
- Seals and protects substrate
- Friendly applicator
- Applied with sprayer, brush or roller
- Easy to clean
- Clear with a slight sheen

Surface Preparation:

Surface must be clean and free of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form release agents or any other contaminants. Remove and repair all loose paint, mortar, stucco, concrete or masonry by water blasting, sand blasting, scraping or using a wire brush. Failure to correctly prepare surface may result in product failure.

Product Specifications:

Packaging:

5 gallon plastic pail - 44.6 lbs.

Coverage:

Coverage will vary due to desired look and the application technique used.

Color:

Applied as a clear or can be tinted to achieve desired effect.

Storage:

Store in a cool, dry place away from direct sunlight.

Clean up:

Clean tools and equipment with water immediately after use.

Shelf Life:

1 year

tuscan stain

Mixing:

Mix with a drill mixer at low speed (100 - 200 rpm) 1 minute or until consistent prior to use.

Application:

Apply Tuscan Stain directly to properly prepared acrylic or cement finishes with a hudson style sprayer, airless sprayer, brush, sponge or roller to achieve desired effect. Job site mock up is recommended prior to application to determine actual application method.

Curing / Drying:

Drying time averages 4 hours depending on ambient temperature, surface, surface temperatures and humidity. Finish fully cures within 2 weeks.

Precaution:

KEEP OUT OF THE REACH OF CHILDREN.
Not for internal consumption.
Do not apply in non-ventilated areas.
Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes.
In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing.
If inhalation causes physical discomfort, remove to fresh air. If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK MEDICAL ATTENTION.
For additional information refer to the material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF THE REACH OF CHILDREN.
NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE ONLY.

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains material listed by the state of California known to cause cancer, birth defects or other reproductive harm.

Technical support:

For technical support call 1-602-272-5830. Information contained in this product Information Guide conforms to the standard detail recommendations and specifications for the installations of Ultrakote Products as of the date published on this document. Ultrakote Products, Inc. assumes no liability, expressed or implied, as to architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact Ultrakote Products, Inc. or visit website at: www.ultrakoteproducts.com