

# tuscano finish

## High Build Smooth Finish



TUSCANO FINISH is an acrylic polymer based, high build, smooth, trowel applied finish.

### Uses:

Tuscano Finish may be used for interior or exterior applications over properly prepared substrates, including new or existing drywall and new or existing plaster substrates.

### Features:

- High build
- Smooth plaster finish
- Low VOC

### Benefits:

- May be used as base coat
- Matches gypsum plaster

### Surface Preparation:

Surface must be clean, dry and free of any bond inhibiting materials. Painted surfaces must be bond tested. Level and prime the entire surface area prior to application to equalize suction rate and to prevent telegraphing lines from appearing through the dried finish.

### Product Specifications:

#### Packaging:

5 gallon plastic pail - 60 lbs.

#### Coverage:

200 - 250 sq. ft. per 5 gallon pail.

Coverage rate will change relative to condition and level of substrate.

#### Color:

12 standard colors.  
Custom colors available upon request.

#### Storage:

Store in a cool, dry interior place. Keep from freezing, out of direct sunlight for long periods and at no time expose to moisture, rain or snow. Storage temperature ranges between 40°F and 95°F.

#### Clean up:

Clean tools and equipment with water immediately after use.

#### Shelf Life:

1 year

# tuscano finish

## High Build Smooth Finish

### Mixing:

Thoroughly mix the Tuscano Finish with a mixer to a homogeneous consistency. A small amount of clean, potable water may be added to adjust workability. When adding color in the field, mix thoroughly to completely disperse all colorant. Always check color against color sample to ensure an accurate match. Close container when not in use. Clean tools with water immediately after use.

### Application:

Tuscano Finish may be applied over finished and primed level 3-5 drywall or properly prepared gypsum or cement plaster base coats. Apply with a stainless steel trowel. Tuscano Finish may also be used as a leveling coat and base coat for smooth Ultrakote finishes over existing heavy textured surfaces. Tuscano Finishes may also be applied in two coats for a smooth troweled finish, upon request special aggregates can be added to produce dragged or pitted textures. First consult an Ultrakote technical representative. Apply Tuscano Finish in a continuous application 1/32" thick and always maintain a wet edge to proper terminations.

### Curing / Drying:

Tuscano Finish will generally dry within 12-24 hours. Surface absorption, temperature and humidity will affect drying time.

### Limitations:

Tuscano Finish should be applied when surface and ambient air conditions are between 40°F and 95°F.

### Technical Data:

Surface burning ASTM E 84 (class A)	Flame spread index:20 Smoke developed index: 5
Mildew/Mold resistance ASTM D 3273	9-10
Water vapor transmission ASTM D 1653	23.9 perms
VOC (g/L)	> 20 g/l

#### Precaution:

KEEP OUT OF THE REACH OF CHILDREN.

Not for internal consumption.

Do not apply in non-ventilated areas.

Use protective equipment such as gloves, eye protection and clothing.

#### First Aid:

In case of eye contact, flush with water at least 15 minutes.

In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION.

Remove and wash contaminated clothing.

If inhalation causes physical discomfort, remove to fresh air. If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK MEDICAL ATTENTION.

For additional information refer to the material Safety Data Sheet (MSDS).

#### Disposal:

Dispose of in accordance with local, state or federal regulations.

#### Warning:

KEEP OUT OF THE REACH OF CHILDREN.

NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE ONLY.

#### Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

#### Prop 65:

This product contains material listed by the state of California known to cause cancer, birth defects or other reproductive harm.

#### Technical support:

For technical support call 1-602-272-5830. Information contained in this product Information Guide conforms to the standard detail recommendations and specifications for the installations of Ultrakote Products as of the date published on this document. Ultrakote Products, Inc. assumes no liability, expressed or implied, as to architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact Ultrakote Products, Inc. or visit website at: [www.ultrakoteproducts.com](http://www.ultrakoteproducts.com)