# SAFETY DATA SHEET



## Foamkote

As of date: March 4, 2016

Section 1	Product Description
Product Name:	Foamkote
Recommended Use:	Cement stucco
Synonyms:	Cement plaster, foam coating, leveling plaster, Polymer modified mortar
Manufacturer:	Ultrakote Products, dba Ultrakote 327 S 27 <sup>th</sup> Ave, Phoenix, AZ 85009, USA 602-272-5830 www.ultrakoteproducts.com
General Phone Number:	602-272-5830 (7am-4pm, AZ Std Time, M-F)
General Fax Number:	602-272-6445

## Section 2 Hazards Identification

Classification of the chemical in accordance with paragraph (d) of 1910.1200;

Signal Word:	Danger
GHS Class:	Serious Eye Damage/Eye Irritation, Category 1, Skin Corrosion/Irritation, Category 2 Skin Sensitizer/Allergic skin reaction, Category 1 Carcinogen/May cause cancer if inhaled, Category 1A, Damage to organs through prolonged or repeated exposure if inhaled, STOT RE 1
Hazard Statements:	<ul> <li>H100s = General, H200s = Physical, H300s = Health, H400s = Environmental</li> <li>H315 Causes skin irritation.</li> <li>H317 may cause an allergic skin reaction.</li> <li>H318 Causes serious eye damage.</li> <li>H350A May cause if inhaled.</li> <li>H372 Causes damage to organs through prolonged or repeated exposure if inhaled.</li> </ul>
Precautionary Statements	<ul> <li>s: P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood</li> <li>P260B - Do not breathe dust.</li> <li>P264.2 - Wash hands thoroughly after handling.</li> <li>P270 - Do not eat, drink, or smoke when using this product</li> <li>P272 - Contaminated work clothing should not be allowed out of the workplace.</li> <li>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>P302+P352A1- IF ON SKIN: Wash with plenty of water.</li> <li>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.</li> <li>P308+P313 - If exposed or concerned: Get medical advice/attention.</li> <li>P314 - Get medical advice/attention if you feel unwell.</li> <li>P321A - Specific Treatment, (see supplementary instructions on the label)</li> <li>P337+313 - If exposed or concerned: Get medical attention.</li> <li>P362+P364 - Take off contaminated clothing and wash before use.</li> </ul>

P405 - Store locked up. P501A - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Ingredients(s) with unknown acute toxicity: None

Hazards not otherwise classified identified during the classification process: None

Section 3	Composition I	nforma	ition and Ingre	edients		
Mixture:						
Component Name	CAS #		<u>WT %</u>	Classification		
Portland Cement	65997-1	15-1	30 - 40%	STOT SE 3, H335: Eye Dam 1,H318 Skin Sens. 1, H317; Skin Irrit. 2 H315		
Silica Sand Calcium Hydroxide Magnesium Hydroxide	14808-6 1305-62 1309-42	2-0	35 - 50%, 1 - 3% 1 - 3%	Carc. 1A, H350A, STOT RE 1, H372A Not classified Not classified		
Section 4	First-Aid Meas	sures				
Emergency and First A	Aid Procedures					
Inhalation:				at rest. If breathing is irregular or stopped, administer n, consult a doctor immediately and show him packing or		
Eyes:	Remove contac	IF IN EYES: Rinse cautiously with water with the eyelids open for a sufficient length of time. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation continues, then get medical advice/attention immediately. Protect uninjured eye.				
Skin Contact:		IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.				
Ingestion:	lf swallowed, do label.	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.				
Most Important sympt	<b>coms/effects, acute</b> Eye Irritation Eye damages Skin Irritation Erythema	and de	layed:			
Indication of any imme	ediate medical atte	ent or ur	nwellness, seek	tment needed: medical advice immediately (show directions for use or		
Section 5	Fire Fighting N	/leasure	es			
Extinguishing Media: Fire Fighting Methods and Protection:		Use carbon dioxide, or water spray when fighting fires involving this material. Firefighters should wear full protective equipment and NIOSH approved self- contained breathing apparatus.				
Fire and/or Explosion Hazards:		Do not inhale explosion and combustion gases. Burning produces heavy smoke.				
Hazardous Combustion Products: Explosive properties: Oxidizing properties:		N.A. N.A. N.A.				
Special protective equ	ipment and preca	utions f				
		Collec discha	arged into drains	ed fire extinguishing water separately. This must not be		

safely.

Section 6	Accid	ental Rel	ease Measu	ires				
Steps to Take in Case Material Is Released or Spilled:		Wear personal protection equipment. Wear breathing apparatus if exposed to vapors/dusts/aerosols. Provide adequate ventilation. Use appropriate respiratory protection. See protective measures under section 7 and 8. Ventilate the contaminated area. Suitable material for taking up: absorbing material, organic, sand. Wash with plenty of water.						
Section 7	Hand	ling and	Storage					
Handling: Storage:			Exercise the localized ve cleaned. Be incompatibl be changed also section handling. W protection.	entilation syste efore making t e material res l before enteri n 8 for recomn /ear protective Keep containe	e when hance m. Don't use ransfer opera- iduals in the ng eating are hended prote gloves/prot	Iling or oper e empty con ations, assu containers. eas. Do not ective equipr ective clothi	ing the c tainer be re that th Contami eat or dri ment. Wa ng/eye p	ontainer. Use fore they have been ere aren't any nated clothing should nk while working. See ash thoroughly after rotection/face
Storage Code	:		N.A.					
Section 8 List of compon	Expos ents with OEL valu <u>OEL Type Country</u>		t <b>rols / Perso</b>	nal Protectio	on Short Term	Short Term	Behavior	Note
-			<u>mg/m3</u>	ppm	<u>mg/m3</u>	<u>ppm</u>		
Silica Sand	ACGIH		0.25					A2-SupsectedHuman Carcinogen; lung cancer, pulmonary fibrosis
Portland cement	ACGIH		1.0					A4- Not classifiable as a Human Carcinogen; pulmonary function: respiratory symptoms: asthma; nasal symptoms
Calcium Hydroxide Magnesium Hydrox			15 15		5 5			
Control Parame Engineering M			General roc	om ventilation	might be rec	uired to ma	intain ope	erator comfort

Personal Protective Equipment (PPE): Respiratory Protection: Respirator Type(s): Eye Protection: General room ventilation might be required to maintain operator comfort under normal conditions of use. Avoid generating airborne dust No respiratory protection required under normal conditions of use. Use NIOSH approved air purifying respirator with dust filter. Wear close fitting safety glasses or goggles when handling this product. Avoid skin contact by wearing clothing that provides comprehensive protection. Wash hands and other exposed areas with mild soap and water before eating,

Gloves:

Section 9 Physical and Chemical Properties

Appearance: Odor: Odor Threshold: pH (Neutrality):

Skin Protection:

Solid, Gray Powder Mild acrylic None 11.0 - 13.0 s.u.

drinking, and when leaving work.

PVC, neoprene, rubber, ntrile

(n-Butyl Acetate=1):N.A.Flammability Classification:N.A.Lower FlammableN.A.Limit in Air (% by vol):N.A.Upper FlammableN.A.Limit in Air (% by vol):N.A.Vapor Pressure (mm of Hg)@20 C:N.A.VAPOR DENSITY (Air=1):N.A.GRAVITY @ 68/68F / 20/20C:Specific Gravity (Water=1):Specific Gravity (Water=1):2.60 - 2.75 g.cm3Pounds/Gallon:N.A.Water Solubility:N.A.Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Other InformationSubstance Groups relevant propertiesSubstance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.NA.N.A.Miscibility:N.A.Mathematical Solubility:N.A.Miscibility:N.A.Miscibility:N.A.Maced Groups relevant propertiesN.A.Maced Groups relevant propertiesN.A.Miscibility:N.A.Conductivity:N.A.	Melting Point/Freezing Point: Boiling Range (Ibp,50%,Dry Point): Flash Point (Test Method): Evaporation Rate	N.A. N.A. N.A.
Flammability Classification:N.A.Lower FlammableN.A.Limit in Air (% by vol):N.A.Upper FlammableN.A.Limit in Air (% by vol):N.A.Vapor Pressure (mm of Hg)@20 C:N.A.VAPOR DENSITY (Air=1):N.A.GRAVITY @ 68/68F / 20/20C:Specific Gravity (Water=1):Pounds/Gallon:N.A.Water Solubility:N.A.Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationSubstance Groups relevant propertiesSubstance Groups relevant propertiesN.A.Fat Solubility:N.A.	•	N.A.
Limit in Air (% by vol):N.A.Upper FlammableI.imit in Air (% by vol):N.A.Vapor Pressure (mm of Hg)@20 C:N.A.VAPOR DENSITY (Air=1):N.A.GRAVITY @ 68/68F / 20/20C:Specific Gravity (Water=1):2.60 - 2.75 g.cm3Pounds/Gallon:N.A.Water Solubility:N.A.Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationSubstance Groups relevant propertiesN.A.Fat Solubility:N.A.	Flammability Classification:	N.A.
Upper FlammableN.A.Limit in Air (% by vol):N.A.Vapor Pressure (mm of Hg)@20 C:N.A.VAPOR DENSITY (Air=1):N.A.GRAVITY @ 68/68F / 20/20C:Specific Gravity (Water=1):Pounds/Gallon:N.A.Water Solubility:N.A.Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationSubstance Groups relevant propertiesSubstance Groups relevant propertiesN.A.Fat Solubility:N.A.	Lower Flammable	
Limit in Air (% by vol): N.A. Vapor Pressure (mm of Hg)@20 C: N.A. VAPOR DENSITY (Air=1): N.A. GRAVITY @ 68/68F / 20/20C: Specific Gravity (Water=1): 2.60 – 2.75 g.cm3 Pounds/Gallon: N.A. Water Solubility: N.A. Partition Coefficient (n-Octane/Water): N.A. Auto Ignition Temperature: N.A. Decomposition Temperature: N.A. Other Information Substance Groups relevant properties N.A. Miscibility: N.A. Fat Solubility: N.A.	Limit in Air (% by vol):	N.A.
Vapor Pressure (mm of Hg)@20 C:N.A.VAPOR DENSITY (Air=1):N.A.GRAVITY @ 68/68F / 20/20C:2.60 – 2.75 g.cm3Pounds/Gallon:N.A.Water Solubility:N.A.Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationSubstance Groups relevant propertiesSubstance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.	Upper Flammable	
VAPOR DENSITY (Air=1):N.A.GRAVITY @ 68/68F / 20/20C:Specific Gravity (Water=1):2.60 - 2.75 g.cm3Pounds/Gallon:N.A.Water Solubility:N.A.Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationSubstance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.	Limit in Air (% by vol):	N.A.
GRAVITY @ 68/68F / 20/20C:Specific Gravity (Water=1):Pounds/Gallon:N.A.Water Solubility:N.A.Partition Coefficient (n-Octane/Water):Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationSubstance Groups relevant propertiesM.A.Miscibility:N.A.Fat Solubility:N.A.	Vapor Pressure (mm of Hg)@20 C:	N.A.
Specific Gravity (Water=1):2.60 - 2.75 g.cm3Pounds/Gallon:N.A.Water Solubility:N.A.Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationN.A.Substance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.		N.A.
Pounds/Gallon:N.A.Water Solubility:N.A.Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationVIAASubstance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.	GRAVITY @ 68/68F / 20/20C:	
Water Solubility:N.A.Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationSubstance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.	Specific Gravity (Water=1):	2.60 – 2.75 g.cm3
Partition Coefficient (n-Octane/Water):N.A.Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationN.A.Substance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.	Pounds/Gallon:	N.A.
Auto Ignition Temperature:N.A.Decomposition Temperature:N.A.Other InformationN.A.Substance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.	Water Solubility:	N.A.
Decomposition Temperature:N.A.Other InformationN.A.Substance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.	Partition Coefficient (n-Octane/Water):	N.A.
Other InformationN.A.Substance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.		N.A.
Substance Groups relevant propertiesN.A.Miscibility:N.A.Fat Solubility:N.A.	Decomposition Temperature:	N.A.
Miscibility: N.A. Fat Solubility: N.A.	Other Information	
Fat Solubility: N.A.	Substance Groups relevant properties	N.A.
	Miscibility:	N.A.
Conductivity: N.A.	Fat Solubility:	N.A.
	Conductivity:	N.A.

#### Section 10

#### **Stability and Reactivity**

Reactivity:
Chemical Stability:
Possibility of Hazardous Reaction:
Conditions to Avoid:
Incompatible Materials:
Hazardous Decomposition Products:

Stable under normal conditions. Stable under normal storage conditions. Keep in dry storage. No dangerous reaction known under conditions of normal use. Stable under normal conditions. None in particular None

## Section 11 Toxicological Information

Toxicological Information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentrations of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological Information on the main components of the mixture:

Silica Sand	a) acute toxicity	LD50 (Oral): 500 mg/kg (Rat)
Calcium hydroxide Magnesium hydroxide		LD50 (Oral): 3000 mg/kg (Rat) LD50 (Oral): 500 mg/kg (Rat)

If not differently specified, the information required in the regulation and listed below must be considered NA.

a) acute toxicity

- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitization
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT single exposure
- I) STOT -repeated exposure
- J) aspiration hazard

Substance(s) listed on the IARC Monographs:

Silica Sand

Group 1

Substance(s) listed as OSHA Carcinogen(s): Silica Sand Substance(s) listed as NIOSH Carcinogen(s): Silica Sand Substance(s) listed on the NTP report on Carcinogens: Silica Sand

Section 12 Ecological Information

**Overview:** 

Adopt good working practices, so that the product is not released into the environment.

**Ecotoxicity:** 

<u>QTY , Chemical Na</u> me 35-50%, Silica Sand	<u>CAS Number</u> 14808-60-7	Eco Toxicity LC 50 a) Aquatic acute toxicity carp >10000.00000 mg/L 72h
1-3 %, Calcium hydroxide	1305-62-0	LC 50 a) Aquatic acute toxicity Fish Cyprinus carpio =1070 mg/L 96h EPA
Persistence and degrada Bioaccumulative potenti Mobility in soil: Other Adverse Effects:		la

## Section 13 Disposal Considerations

Disposal Methods:

Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance. Not Determined

Waste Disposal Code(s):

Section 14 Transport I	nformation
UN number	
ADR-UN number:	N/A
DOT-UN number:	N/A
IATA-UN number:	N/A
IMDG-UN number:	N/A
UN proper shipping name	
ADR-Shipping Name:	N/A
DOT Proper Shipping Name:	N/A
IATA-Technical name:	N/A
IMDG-Technical name:	N/A
Transport hazard class(es)	
ADR- Class:	N/A
DOT Hazard Class:	N/A
IATA- Class:	N/A
IMDG-Class:	N/A
Packing qroup	
ADR Packing Group:	N/A
DOT-Packing group:	N/A
IATA-Packing group:	N/A
IMDG-Packing group:	N/A
Environmental hazards	
Marine pollutant:	No
Environmental Pollutant:	N.A.
Transport in bulk according to Annex II	
	N.A.
Special Precautions	
Department of Transportation (DOT):	
DOT-Special Provision(s):	N/A
DOT Label(s):	N/A

DOT S	ymbol:	N/A			
DOT C	argo Aircraft:	N/A			
DOT P	assenger Aircraft:	N/A			
DOT B	ulk:	N/A			
DOT N	on-Bulk:	N/A			
Road and Rail (ADR-RID):					
ADR-L	abel:	N/A			
ADR H	azard identification number:	N/A			
ADR T	unnel Restriction Code:	N/A			
Air ( IATA) :					
ÍÁTA- I	Passenger Aircraft:	N/A			
IATA- (	Cargo Aircraft :	N/A			
IATA- I	_abel:	N/A			
IATA- S	Subrisk:	N/A			
IATA- I	Erg:	N/A			
IATA- S	Special Provisions:	N/A			
Sea (IMDG):					
IMDG ·	-Stowage Code:	N/A			
IMDG ·	-Stowage Note:	N/A			
IMDG ·	-Subrisk:	N/A			
IMDG ·	-Special Provisions:	N/A			
IMDG ·	-Page:	N/A			
IMDG ·	-Label:	N/A			
IMDG ·	-EMIS:	N/A			
IMDG ·	-MFAG:	N/A			

## Section 15

## **Regulatory Information**

#### **USA - Federal regulations**

TSCA • Toxic Substances Control Act TSCA Inventory: All the components are listed on the TSCA inventory

TSCA listed substances:

Silica Sand	is listed in TSCA	Section 8b
Portland cement	is listed in TSCA	Section 8b
Calcium hydroxide	is listed in TSCA	Section 8b

SARA - Superfund Amendments and Reauthorization Act Section 302 – Extremely Hazardous Substances: no substance listed

Section 304 – Hazardous substances:	no
Section 313 – Toxic chemical list:	no

CERCLA – Comprehensive Environmental Response, Compensations, and Liability Act Substance(s) listed under CERCLA: no substance listed

CAA – Clean Air Act CAA Substances listed:

no substance listed

substance listed substance listed

CWA – Clean Water Act CWA Substances listed:

no substance listed

#### **USA - state specific regulations**

California Proposition 65 Substance(s) listed under California Proposition 65 Silica Sand listed as carcinogen

Massachusetts right to know Substance(s) listed under Massachusetts Right to Know; Silica Sand Portland cement Calcium hydroxide


Pennsylvania Right to know Substance(s) listed under Pennsylvania Right to Know; Silica Sand Portland cement Calcium hydroxide

New Jersey Right to know Substance(s) listed under New Jersey Right to Know; Silica Sand Portland cement Calcium hydroxide

### Section 16

**Other Information** 

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.



HMIS Health:	2 = MODERATE
HMIS Health	<ul> <li>Is health hazard chronic?: Yes</li> </ul>
HMIS Flammability:	0 = Not Combustible
HMIS Reactivity:	0 = MINMAL
HMIS P.P.E.:	Safety glasses, gloves, dust respirators

NFPA Health:	2 = MODERATE
NFPA Flammability:	0 = Not Combustible
NFPA Reactivity:	0 = MINIMAL
NFPA Special Risk:	NONE

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Cause serious eye damage.
H335	May cause respiratory irritation.
H350A	May cause cancer if inhaled
H372A	Causes damage to organs through prolonged or repeated exposure if inhaled

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Texrite makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

### Glossary

ACGIH	-American Conference of Governmental	CERCLA	A -Comprehensive Environmental Response,
	Industrial Hygienists		Compensation, and Liability Act
CAS	-Chemical Abstract Service Number	DOT	-U.S. Department of Transportation

IARC	-International Agency for Research on	
	Cancer	
N/A	-Not Available	
NTP	-National Toxicology Program	
OSHA	-Occupational Safety and Health	
	Administration	
PEL	-Permissible Exposure Limit	
ppm	-Parts per million	

## End of Safety Data Sheet

- RCRA -Resource Conservation and Recovery Act
- SARA -Superfund Amendments and Reauthorization
- TLV -Threshold Limit Value
- TSCA -Toxic Substances Control Act
- IDLH -Immediately dangerous to life and health