

acrylic adhesive

100% Acrylic Based EPS Adhesive



ACRYLIC ADHESIVE is a 100% acrylic based material that is designed to be an EPS insulation board adhesive.

Uses:

Acrylic Adhesive is primarily used as an adhesive for adhering EPS insulation board to approved substrates.

Features:

- Versatile
- User friendly

Benefits:

- Can be used over multiple prepared substrates
- Mixes easily with long open time

Surface Preparation:

Surface must be clean and free of bonding-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents or any other contaminants. Remove and repair any loose paint, mortar, stucco, concrete or masonry by water blasting, sand blasting, scraping or using a wire brush. Substrate should be sound and securely fastened.

Mixing:

Mix Acrylic Adhesive with a drill mixer and jiffler paddle before each use.

Product Specifications:

Packaging:

5 gallon plastic pail 65 lbs.
(29.41 kg)

Coverage:

Approximate coverage as adhesive: 200 sq. ft.

Color:

Off-white

Storage:

Store in cool dry place away from direct sunlight.

Clean up:

Clean tools immediately after use. Remove all debris from the surrounding areas immediately following the application process.

Shelf Life:

1 year

acrylic adhesive

100% Acrylic Based EPS Adhesive

Application:

Apply Acrylic Adhesive to the back of the EPS board using a 3/8 notch trowel. Angle the trowel so that the thickness of the adhesive would be about 3/8". Immediately place the insulation board on the substrate and slide into position. Apply equal pressure to the surface of the board. Abut the edges of the board tightly. Do not allow the adhesive to form a skin before positioning the insulation board on the substrate. Do not allow the adhesive to get into the board joints.

Curing / Drying:

Acrylic Adhesive needs to be protected from rain and allowed to cure for at least 24 hours.

Limitations:

Acrylic Adhesive should be applied when surface and ambient conditions are between 40°F and 110°F during application and cure time. Weather conditions may affect drying time.

Precaution:

KEEP OUT OF THE REACH OF CHILDREN.

Not for internal consumption.

Do not apply in non-ventilated areas.

Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes.

In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing.

If inhalation causes physical discomfort, remove to fresh air. If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK MEDICAL ATTENTION.

For additional information refer to the material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF THE REACH OF CHILDREN.

NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE ONLY.

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains material listed by the state of California known to cause cancer, birth defects or other reproductive harm.

Technical support:

For technical support call 1-602-272-5830. Information contained in this product Information Guide conforms to the standard detail recommendations and specifications for the installations of Ultrakote Products as of the date published on this document. Ultrakote Products, Inc. assumes no liability, expressed or implied, as to architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact Ultrakote Products, Inc. or visit website at: www.ultrakoteproducts.com