

admix

Waterborne Acrylic Admix



ULTRAKOTE ADMIX is a concentrated water-borne acrylic polymer additive for use with cementitious material.

Uses:

Ultrakote Admix, when diluted, is added to cementitious materials to reduce cracking and shrinkage while improving tensile, flexural and compressive strength. When added to cementitious material, Ultrakote Admix will produce a polymer modified cement that will increase freeze / thaw stability.

Features:

- Produces polymer modified cement
- Improves tensile, flexural and compressive strength
- Reduces cracking and shrinkage

Benefits:

- Superior strength
- Water resistance and aging characteristics
- Better durability

Surface Preparation:

Surface must be clean and free of bonding-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents or any other contaminants. Remove and repair any loose paint, mortar, stucco, concrete or masonry by water blasting, sand blasting, scraping or using a wire brush. Repair all cracks. If applying over painted surface, test paint to make sure it is load bearing. Failure to correctly prepare the surface may result in product failure.

Product Specifications:

Packaging:

1 gallon plastic bottle - 8 lbs (3.6 kg)

Color:

White liquid

Storage:

Store in cool dry place away from direct sunlight.

Clean up:

Clean tools immediately after use. Remove all debris from the surrounding areas immediately following the application process.

Shelf Life:

1 year

admix

Waterborne Acrylic Admix

Mixing:

Shake vigorously before use. In a clean plastic pail, mix 1 quart of Ultrakote Admix with 3 quarts potable water. Reduce dilution ratio for greater polymer modification. Add this mix to any cementitious material that requires polymer modification.

Limitations:

Do not use when ambient or surface temperature is below 40°C.

Precaution:

KEEP OUT OF THE REACH OF CHILDREN.

Not for internal consumption.

Do not apply in non-ventilated areas.

Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes.

In case of skin contact, wash affected areas with soap and water.

If irritation persists, SEEK MEDICAL ATTENTION.

Remove and wash contaminated clothing.

If inhalation causes physical discomfort, remove to fresh air.

If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK MEDICAL ATTENTION.

For additional information refer to the material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF THE REACH OF CHILDREN.

NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE ONLY.

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains material listed by the state of California known to cause cancer, birth defects or other reproductive harm.

Technical support:

For technical support call 1-602-272-5830. Information contained in this product Information Guide conforms to the standard detail recommendations and specifications for the installations of Ultrakote Products as of the date published on this document. Ultrakote Products, Inc. assumes no liability, expressed or implied, as to architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact Ultrakote Products, Inc. or visit website at: www.ultrakoteproducts.com