

stuccokote

Epoxy / Acrylic Exterior Paint



STUCCOKOTE is an epoxy / acrylic decorative and protective exterior paint used over Ultra-flex, Duratex, Ultrakote Spanish Texture, Ultrakote Sand Finish and field mixed finished.

Uses:

Stuccokote is an exterior acrylic paint designed for use over high pH surfaces as stucco, prepared masonry or concrete and has an excellent adhesion to primed metal and wood surfaces.

Features:

- Weather resistant
- Exterior application
- Good gloss retention

Benefits:

- Greater protection for longer periods
- Greater flexibility for longer life
- Increased ease in surface cleaning

Surface Preparation:

Surface must be clean and free of bonding-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents or any other contaminants. Remove and repair any loose paint, mortar, stucco, concrete or masonry by water blasting, sand blasting, scraping or using a wire brush. Repair all cracks with approved patching compound. If applying over a painted surface, test paint to make sure it is load bearing.

Product Specifications:

Packaging:

5 gallon plastic pail 50 lbs.
(22.6 kg)

Coverage:

Approximate coverage is 500 - 750 sq. ft. per pail @ 4 mils. Dry thickness (coverage will vary depending on substrate, surface texture and application technique.)

Color:

All Ultrakote Standard Colors and custom colors on written request.

Storage:

Store in cool dry place away from direct sunlight.

Clean up:

Clean tools immediately after use. Remove all debris from the surrounding areas immediately following the application process.

Shelf Life:

1 year

stuccokote

Epoxy / Acrylic Exterior Paint

Mixing:

Prior to use, mix with drill mixer for 1 minute or until consistent. One quart (16 oz.) of potable water may be added to 5 gallons to adjust workability.

Application:

Stuccokote may be applied by roller, brush or spray equipment (spray tip should be a 5-19 through a 6-23). Always apply Stuccokote in a continuous application, working to a wet edge to eliminate cold joints.

Curing / Drying:

Drying time averages 3 hours depending on ambient temperature, humidity and film thickness. Stuccokote will dry completely within 12-24 hours.

Limitations:

Stuccokote should be applied when surface and ambient conditions are between 45°F and 100°F and should be protected from wet weather for a minimum of 24 hours. Substrate must have a pH of 12 or lower. Stuccokote has excellent bonding to almost any surface except certain plastics, rubber, metal and mastics. Glossy surfaces should be sanded prior to application.

Precaution:

KEEP OUT OF THE REACH OF CHILDREN.

Not for internal consumption.

Do not apply in non-ventilated areas.

Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes.

In case of skin contact, wash affected areas with soap and water.

If irritation persists, SEEK MEDICAL ATTENTION.

Remove and wash contaminated clothing.

If inhalation causes physical discomfort, remove to fresh air.

If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK MEDICAL ATTENTION.

For additional information refer to the material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF THE REACH OF CHILDREN.

NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE ONLY.

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains material listed by the state of California known to cause cancer, birth defects or other reproductive harm.

Technical support:

For technical support call 1-602-272-5830. Information contained in this product Information Guide conforms to the standard detail recommendations and specifications for the installations of Ultrakote Products as of the date published on this document. Ultrakote Products, Inc. assumes no liability, expressed or implied, as to architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact Ultrakote Products, Inc. or visit website at: www.ultrakoteproducts.com