

tuscany accent



TUSCANY ACCENT is a stain used in combination with Ultrakote finishes to achieve an “old world” or “antique” appearance.

Uses:

Tuscany Accent is for interior or exterior applications when the “old world” or “antique” look is desired.

Surface Preparation:

Surface for the Tuscany Accent stain should be a “just applied” or “wet” layer of Ultrakote finish.

Mixing:

Stir the jar vigorously before use.

Application:

Apply one coat of Ultrakote finish as directed (see specific finish product data sheets) with a stainless steel trowel or approved spray equipment. Allow to dry cure out completely. Apply a second layer of Ultrakote finish. While the second coat is still wet randomly spray Tuscany Accent within your working area using a spray bottle. Work the stain into the finish with a stainless steel pool finishing trowel. Randomly add more Tuscany Accent stain until the desired look is achieved.

Curing / Drying:

Drying time averages 4 hours depending on the ambient temperature, surface, surface temperatures and humidity. Finish fully cures within two weeks.

Product Specifications:

Packaging:

32 oz. container

Coverage:

Dry thickness (coverage will vary depending on substrate, surface texture and application technique.)

Color:

All Ultrakote Standard Colors and custom colors on written request.

Storage:

Store in cool dry place away from direct sunlight.

Clean up:

Clean tools immediately after use. Remove all debris from the surrounding areas immediately following the application process.

Shelf Life:

1 year

Precaution:

KEEP OUT OF THE REACH OF CHILDREN.

Not for internal consumption.

Do not apply in non-ventilated areas.

Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes.

In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing.

If inhalation causes physical discomfort, remove to fresh air. If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK MEDICAL ATTENTION.

For additional information refer to the material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF THE REACH OF CHILDREN.

NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE ONLY.

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains material listed by the state of California known to cause cancer, birth defects or other reproductive harm.

Technical support:

For technical support call 1-602-272-5830. Information contained in this product Information Guide conforms to the standard detail recommendations and specifications for the installations of Ultrakote Products as of the date published on this document. Ultrakote Products, Inc. assumes no liability, expressed or implied, as to architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact Ultrakote Products, Inc. or visit website at: www.ultrakoteproducts.com